

### PRODUCT

<b>Installation</b>	Float, Glue Down
<b>Wear Layer</b>	20 mil with Quantum X™ Technology (Prop 65 Compliant)
<b>Wear Finish</b>	1 coat UV-cured acrylic Gloss Level: 4%-6%
<b>Core</b>	6mm Multi-layered Rigid Core (Stone & virgin DOTP Composite (Not a single extrusion SPC))
<b>Underlayment</b>	1mm IXPE (No VOCs)

### SIZE/PACKAGING

<b>Plank Size</b>	9"x72"
<b>Planks/Carton</b>	4
<b>SF/Carton</b>	17.67
<b>Cartons/Pallet</b>	52
<b>SF/Pallet</b>	918.84

### TEST DATA

<b>Static Load Limit</b>	ASTM F970-07	0.001 inch - Passes greater than 250 psi
<b>Dynamic Load Limit</b>	ASTM D1037	2200 PSI
<b>Dynamic Coefficient of Friction</b>	ASTM E303	0.38 DCOF (Wet slip resistance) Low Risk Classification
<b>Critical Radiant Flux</b>	ASTM-E648	Meets or exceeds, Class 1
<b>Impact Sound Conduction</b>	ASTM E492-09	IIC 63db
<b>Airborne Sound Conduction</b>	ASTM E90-09	STC 62db
<b>Color Resistance to Heat</b>	ASTM F1514	Meets <8.0 ΔE Requirement
<b>Color Resistance to Cold</b>	ASTM F1514	Meets <8.0 ΔE Requirement
<b>Thermal Resistance</b>	ASTM C518	R Value -0.6
<b>Thickness Swell</b>	NALFA 3.2	Class 4, Heavy Commercial
<b>Xenon Light Resistance</b>	NALFA 3.3	Class 4, Heavy Commercial
<b>Cleanability-Stain Resistance</b>	NALFA 3.4	Class 4, Heavy Commercial
<b>Large Ball Impact Resistance</b>	NALFA 3.5	Class 4, Heavy Commercial
<b>Small Ball Impact Resistance</b>	NALFA 3.6	Class 4, Heavy Commercial
<b>Dimensional Stability</b>	NALFA 3.8	Class 4, Heavy Commercial
<b>Caster Chair</b>	NALFA 3.9	Class 3, Commercial
<b>Surface Bonding</b>	NALFA 3.10	1.31 N/mm - Exceeds Class 3, Commercial
<b>Residual Indent</b>	NALFA LF 01-2011	0mm, Clause 3.1 – Heavy Commercial Rated - 8 Mpa (>1160 PSI)

### OTHER

<b>Certifications</b>	FloorScore Certified / VOC Free / 100% Waterproof / Prop 65 Compliant Wear Layer
<b>Country of Origin</b>	Manufactured in China

